

Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: illbruck PU700

· MSDS code: A-I-PU700

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Productie B.V. Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

#### · Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

### 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

#### · 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 1)

### · Hazard pictograms







GHS02 GHS07 GHS08

### · Signal word Danger

#### · Contains:

diphenylmethanediisocyanate, isomers and homologues

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P284 In case of inadequate ventilation wear respiratory protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### · Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· **Description:** Active substance with propellant

· Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	

(Contd. on page 3)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

	(0	Contd. of page 2)
EC number: 911-815-4	tris(2-chloro-1-methylethyl)phosphate	10-<20%
Reg.nr.: 01-2119486772-26-xxxx	Acute Tox. 4, H302	
CAS: 9082-00-2	Ethoxylated/propoxylated glycerol	10-<20%
	Acute Tox. 4, H302	
CAS: 25791-96-2	Glycerol, propoxylated	10-<20%
NLP: 500-044-5	Acute Tox. 4, H302	
CAS: 115-10-6	dimethyl ether	5-<10%
EINECS: 204-065-8	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27-xxxx		
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21-xxxx		

#### · SVHC -

#### · Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2)

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

Immediately remove all soiled and contaminated clothing

#### · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Irritating to eyes, respiratory system and skin.

Nausea

Harmful if inhaled.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.

(Contd. on page 4)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Ensure adequate ventilation.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Keep away from sources of ignition - No smoking.

Do not breathe vapour.

Avoid contact with the eyes and skin.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 5)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 4)

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

The usual precautionary measures are to be adhered to when handling chemicals.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from water.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

### CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

CAS: 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

· DNELs

### · Long term effects

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homolog
---

Inhalative industrial 10.05 mg/m2 (workers) (avetemic and least offerts)

irinalative Industrial	0.05 mg/ms (workers) (systemic and local effects)
consumer	0.025 mg/m3 (general public) (systemic and local effects)

### tris(2-chloro-1-methylethyl)phosphate

Oral	consumer	0.52 mg/kg/24h (general public) (systemic effects)
Dermal	industrial	2.08 mg/kg/24h (workers) (systemic effects)
	consumer	1.04 mg/kg/24h (general public) (systemic effects)
Inhalative	industrial	5.82 mg/m3 (workers) (systemic effects)

(Contd. on page 6)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

Trado Harrio. Historia 700				
			(Contd. of page 5)	
		1.46 mg/m3 (general public) (systemic effects)		
	15-10-6 dime	_ <del>-</del>		
Inhalati	ve industrial	1,894 mg/m3 (workers) (systemic effects)		
	consumer	471 mg/m3 (general public) (systemic effects)		
· Short t	erm effects			
CAS: 9	016-87-9 diph	nenylmethanediisocyanate, isomers and homologues		
Oral	consumer	20 mg/kg/24h (consumers) (systemic effects)		
Dermal	industrial	50 mg/kg/24h (workers) (systemic and local effects)		
	consumer	25 mg/kg/24h (consumers) (systemic effects)		
Inhalati	ve industrial	0.1 mg/m3 (workers) (systemic and local effects)		
	consumer	0.05 mg/m3 (general public) (local effects)		
tris(2-c	hloro-1-meth	ylethyl)phosphate		
Dermal	industrial	8 mg/kg/24h (workers) (systemic effects)		
	consumer	4 mg/kg/24h (general public) (systemic effects)		
Inhalati	ve industrial	22.4 mg/m3 (workers) (systemic effects)		
	consumer	11.2 mg/m3 (general public) (systemic effects)		
· PNECs	}			
CAS: 9	016-87-9 dipl	nenylmethanediisocyanate, isomers and homologues		
PNEC	1 mg/L (fresh	water)		
	10 mg/L (inter	rmittent release)		
	0.1 mg/L (salt	water)		
tris(2-c	hloro-1-meth	ylethyl)phosphate		
PNEC	0.64 mg/L (fre	esh water)		
	0.064 mg/L (r	narine)		
PNEC	1.7 mg/kg dw	t (soil)		
1.34 mg/kg dwt (sediment (salt water))				
CAS: 1	CAS: 115-10-6 dimethyl ether			
PNEC 0.155 mg/L (fresh water)				
	160 mg/L (sev	wage treatment plant)		
	1.549 mg/L (ii	ntermittent release)		
	0.016 mg/L (s	alt water)		
PNEC	0.045 mg/kg (	(soil)		
	0.069 mg/kg (	(sediment (salt water))		
Additio	nal Occupati	onal Exposure Limit Values for possible hazards during proce	ssina:	

- · Additional Occupational Exposure Limit Values for possible hazards during processing: Carbon dioxide (CO2)
- · Additional information: The lists valid during the making were used as basis.

(Contd. on page 7)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 6)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

### Material of gloves

Butyl rubber, BR

Recommended thickness of the material: > 0.7 mm

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

### · Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· Eye protection:



Tightly sealed goggles

### Body protection:



Protective work clothing

- GB

(Contd. on page 8)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 7)

SECTION 9: Physical and chemical properties		
<ul> <li>9.1 Information on basic physical and</li> <li>General Information</li> <li>Appearance:</li> </ul>	chemical properties	
Form: Colour: Odour: Odour threshold:	Aerosol According to product specification Characteristic Not determined.	
<ul> <li>pH-value:         <ul> <li>Melting point/freezing point:</li> </ul> </li> <li>Initial boiling point and boiling range:</li> </ul>	Not determined. Not applicable, as aerosol. Undetermined.	
· Flash point:	-97 °C	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	3.0 Vol % 18.6 Vol %	
· Vapour pressure at 20 °C:	5200 hPa	
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	1.02 g/cm³ Not determined. Not applicable.	
· Solubility in / Miscibility with water:	Immiscible / difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: VOC (EU) VOC (EC) · 9.2 Other information	153.0 g/l 15.00 % No further relevant information available.	



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 8)

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Danger of bursting.

Forms explosive gas mixture with air.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (prussic acid)

### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:				
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues				
Oral	LD50	>10,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	1.5 mg/L (rat)		
tris(2-chloro-1-methylethyl)phosphate				
Oral	LD50	632 mg/kg (rat)		
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol				
Oral	LD50	>500 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		
CAS: 25791-96-2 Glycerol, propoxylated				
Oral	LD50	1,999 mg/kg (rat)		

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

(Contd. on page 10)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 9)

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

Suspected of causing cancer.

- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

|--|

### CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

LC0/96 h >1,000 mg/L (brachydanio rerio)

EC50/24 h > 1,000 mg/L (daphnia magna)

### tris(2-chloro-1-methylethyl)phosphate

LC50/96 h 51 mg/L (pimephales promelas)

### CAS: 9082-00-2 Ethoxylated/propoxylated glycerol

LC50/48 h >100 mg/L (brachydanio rerio)

EC50/48 h > 100 mg/L (daphnia magna)

EC50/72 h >1,000 mg/L (scenedesmus capricornutum)

- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is not easily biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

### · Ecotoxical effects:

### CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d >10 mg/L (daphnia magna)

### Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

(Contd. on page 11)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 10)

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Do not pierce or burn, even after use.

· European waste catalogue			
16 05 04* gases in pressure containers (including halons) containing hazardous substances			
08 05 01*	waste isocyanates		
HP3	Flammable		
HP4	Irritant - skin irritation and eye damage		
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
HP6	Acute Toxicity		
HP7	Carcinogenic		
HP13	Sensitising		

- · Uncleaned packaging:
- · Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

### **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR



· Class 2 5F Gases.

· Label 2.1

(Contd. on page 12)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

· Tunnel restriction code

(Contd. of page 11) · IMDG, IATA · Class 2.1 · Label 2.1 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. Danger code (Kemler): · EMS Number: F-D.S-U Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: Limited quantities (LQ) 1L **Excepted quantities (EQ)** Code: E0 Not permitted as Excepted Quantity · Transport category 2

D

(Contd. on page 13)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 12)

· IMDG

· Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

### **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) 2001/118/EC as regards the list of wastes

2008/98/EC on waste

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 14)



Printing date 19.12.2019 Version number 9 Revision: 04.04.2019

Trade name: illbruck PU700

(Contd. of page 13)

### Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

\* Data compared to the previous version altered.

GD